

# RI. The one.

A lighter, re-calibrated Deltabox III chassis with idealised stiffness balance, new suspension settings and a relocated engine and swingarm deliver unsurpassed cornering performance. Aesthetically, the bike's sharp new lines and refined image place the R1 in a completely different category from competing machines in its genre. The new R1. A riding experience like no other.

by anything in its category.

## What's New



#### Frame

The R1's new Deltabox III aluminium frame with long, GP-style swingarm relocates the engine 20 mm higher and the swingarm pivot 18.5 mm higher and has been completely redesigned for idealised stiffness balance. The result is exceptionally responsive handling performance on winding roads.



Headlight

The R1's dual, multi-reflector headlights, the aggressive lines and the purified design highlights the single minded focus of the new R1.



#### Engine

Awesome! The combination of fuel injection, a new, more sophisticated EXUP and improved shifting make this liquid-cooled, 998 cc, DOHC, 5-valve engine a perfect match for the new chassis' exceptional cornering performance. The result? Greater throttle response throughout the rev range, more drive out of corners and awesome top



#### Fuel Injection

Yamaha's new fuel injection system offers all the benefits of fuel injection, such as easy starting, enhanced response and reduced emissions (meets EU2 standards). The secret? Suction pistons fitted to the throttle bodies supply the engine with the ideal air volume at all rpm for stable output across the rev range.



#### rant Eucnansian/Prakas

The R1's new, fully-adjustable 43 mm upside-down forks have been thoroughly re-calibrated and stiffness balanced to match the new frame. Stiffer springs, a shorter stroke and smoother, more sensitive action contribute to improved rider feedback. Large-diameter 298 mm front discs are more heat-resistant and are gripped by powerful, new-generation R1 brakes with orange-coloured, monobloc, 4-piston calipers.



#### Poor Sucroncion/Proko

New aluminium swingarm operates a fully-adjustable rear shock with piggyback reservoir to reduce heat-induced shock fade. Revised settings contribute to the bike's superbly balanced cornering performance. Compact rear disc with new-generation R1 monobloc caliper ensures balanced braking.

The purest sensation in sport riding is yours to experience on the brilliant new YZF-R1. Completely uprated in engine,

from a host of performance-enhancing modifications, foremost of which is an advanced fuel injection system.

chassis and styling, this sensational machine combines exceptional cornering performance with a look and feel unmatched

Already the most sophisticated open-class engine on the market, the R1's liquid-cooled 5-valve power unit benefits



#### Instrumentation

Lightweight cockpit instrumentation includes a high-visibility analog tacho, backed by LED speedo and multi-function LED displays to keep you fully aware of how this high-performance machine is performing. Innovative new rideradjustable shift-point indicator lets you tailor the shift rpm to suit riding and road conditions.



#### Seat Cowl/Tail ligh

The new seat cowl would look right at home on a fighter aircraft. High-visibility, integrated LED tail light highlights the advanced technology of this sophisticated piece of machinery.

ENGINE	
Туре	Liquid-cooled, 4-stroke, forward inclined parallel 4-cylinder, DOHC, 20 valves
Displacement	
	74 x 58 mm
Max. power	111.8 kW (152 HP) @ 10,500 rpm
Max. torque	104.9 Nm (10.7 kg-m) @ 8,500 rpm
Lubrication	Wet sump
Fuel supply	Electronic fuel injection
	Wet, multiple-disc
	TCI (digital)
Starter system	Electric
Transmission	Constant mesh, 6-speed
rillai transiinssion	

CHASSIS	
Front suspension	Telescopic fork
Front wheel travel	
Rear suspension	Swinging arm (Link-type suspension)
Rear wheel travel	
Front brake	Dual discs, Ø 298 mm
Rear brake	Single disc, Ø 220 mm
Front tyre	
	190/50 ZR17M/C (73W)

DIMENSIONS	
Overall length	2,035 mm
Overall width	. 705 mm
Overall height	1,105 mm
Seat height	. 820 mm
Wheelbase	1,395 mm
Min. ground clearance	. 140 mm
Dry weight	174 kg
Fuel tank capacity	. 17 litres
Oil tank capacity	3.8 litres

Always wear a helmet, eye protection and protective clothing. Yamaha encourage you to ride safely and respect fellow riders and the environment. The specification and appearance of Yamaha products can vary from time to time without notice, and as shown here are illustrative only and are not a contractual description of products. For further details please consult your Yamaha dealer.









If you prefer a more race-inspired look you have the option of a deep purplish blue colour scheme that incorporates the famous Yamaha speedbar-type graphics.



TOUCHING YOUR HEART

DEALER

### YAMAHA MOTOR (UK) LTD

Sopwith Drive, Brooklands
Weybridge, Surrey KT13 OUZ
Tel.: 01932 358000
Information hotline: 01932 358121
Brochure email: brochure@yamaha-motor.co.uk
Website: www.yamaha-motor.co.uk

YAMAHA MOTOR (UK) LTD use and recommend Mobil Oil



