
YAMAHA YZF1000RThunderace



YZF1000R Thunderace. Riding the storm.

The day of reckoning has arrived. From this moment on things are about to change. Because the new Thunderace is ready.

And it has got the muscle to get its own way. Every time!

Short wheelbase Deltabox chassis has been lifted straight from our World Championship Superbike racers to give this new generation supersport bike ultra responsive handling.

Featuring fully adjustable suspension systems, lightweight high performance brakes and wide section radials, the mighty YZF-R is built to blitz your favourite twisty back road!

Packing a massive mid to high rpm punch, the 1,000 cc slant block engine blasts out phenomenal standing start and roll on acceleration that has to be experienced to be believed.

And with the most radical low drag bodywork ever seen in the supersport category, this is a machine no one can ever ignore.

Or hide from.







YZF1000R TECHNICAL SPECIFICATIONS

ENGINE



- Engine One litre slant block
- design
- 5-valve heads
- * Massive power output



- * High durability forged pistons
- Low reciprocating weight
- Excellent throttle pickup

TypeLiquid-cooled, 4-stroke DOHC,
Forward inclined parallel 4-cylinder
Displacement1,002 cc
Bore and stroke75.5 x 56.0 mm
Compression ratio11.5:1
Max. power
(DIN)145 HP (106.7 kW) @ 10000 rpm
(ISO)137.8 HP (103 kW) @ 10000 rpm
Max. torque11 kg-m (108 Nm) @ 8500 rpm
Starting systemElectric



Carburettors

- New 38 mm down-draft carburettors
- Throttle Position
- Sensor (TPS) Instantaneous response

Carburation	BDSR38 x 4
Lubrication	Wet sump
TRANSMISSION	



Transmission

- Smooth action clutch
- 5-speed transmission
- * slick shifting design

Primary reduction ratio68/41 (1.659)
Secondary reduction ratio46/17 (2.706)
Transmission type5-speed constant mesh
Gear ratio 1st36/14 (2.571)
Gear ratio 2nd32/18 (1.778)
Gear ratio 3rd29/21 (1.381)
Gear ratio 4th27/23 (1.174)
Gear ratio 5th28/27 (1.037)
Final transmissionChain
IgnitionT.C.I. (Digital)



CHASSIS



FI	ame
*	High regidity
	aluminium Deltah

frame Short wheelbase YZF Superbike based geometry

Overall length	2,085 mm
Overall width	735 mm
Overall height	1,170 mm
Seat height	795 mm
Wheelbase	1,435 mm
Minimum ground clearance	135 mm
Dry weight	
Caster angle	24°
Trail	97 mm
Fuel tank capacity	
Fuel reserve amount	4 L

SUSPENSION



Front forks

- Cartridge type front forks
- Fully adjustable
- Flex resistant 48 mm tubes





- Monocross rear suspension
- * Fully adjustable
- * Lightweight aluminium swinging arm

	Telescopic fork
Front shock	Rebound/compression
	adjustable
Front fork travel	120 mm
Rear suspension	Monocross
Rear shock	Rebound/compression
	adjustable
Rear shock travel	65 mm
Front wheel travel	120 mm
Rear wheel travel	120 mm
Front tyre size	120/70 ZR17
	180/55 ZR17



FRONT WHEEL

Rim size	MT3.50 x 17
Rim material	Aluminium
REAR WHEEL	
Rim size	MT5.50 x 17
Pim material	Aluminium



- * High traction radial tvres
- 120/70 ZR17 front
- * 180/55 ZR17 rear Wheels
- Cast alloy wheels
- * Hollow 3-spoke design
- * Low unsprung weight

BRAKES

Front brake type....Dual disc brakes (298 mm) Rear brake typeSingle disc brake (245 mm)





Front/Rear brake

- 298 mm dual front discs/4-pot callipers
- * 245 mm rear disc/2-pot calliper





Always wear a helmet, eye protection and protective clothing. Yamaha encourage you to ride safely and respect fellow riders and the environment. Specifications and appearance of Yamaha products shown here may vary according to requirements and conditions, and are subject to change without notice. For further details, please consult your Yamaha dealer.

DEALER

Yamaha Motor (U.K.) Ltd.

Sopwith Drive The Brooklands Industrial Park Brooklands, Weybridge, Surrey KT13 OUZ Tel.:0932-35 80 00



