



Extreme technology. Supreme capability.


In today's highly competitive supersport scene there is one powerplant that commands total respect.

Running with a special 5-valve head design, advanced downdraft carburettors, torque-boosting EXUP and a low centre of gravity slant-block layout, the new generation YZF1000R engine represents the cutting edge in high-performance powerplant design.

No other large-capacity supersport motorcycle comes close to challenging the Thunderace's superbike racer-based specification.

And out in the real world of sweeping bends and snaking mountain passes the YZF's mind-bending acceleration and outrageous full-on performance push the supersport experience right to the edge.







Programmed for the ultimate experience.

Based around the short wheelbase dimensions used on our World Superbike racers, the YZF1000R's aluminium Deltabox chassis combines extremely low weight with enormous rigidity—the two essentials for precision handling.

Running with fully adjustable suspension, super-efficient triple disc braking system and a remarkably comfortable riding position for a supersport bike, the latest Thunderace has got to be one of the most balanced total packages in the class.





YZF1000R Thunderace Technical Specifications ENGINE

Carburation BDSR38 x 4

Fuel reserve amount 4,5 litres

TRANSMISSION

Gear ratio 1st	36/14 (2.571)
Gear ratio 2nd	32/18 (1.778)
Gear ratio 3rd	29/21 (1.381)
Gear ratio 4th	27/23 (1.174)
Gear ratio 5th	28/27 (1.037)
Final transmission	Chain
Ignition	T.C.I. (digital)

CHASSIS

mn
mn
mn
mr
mr
8 k
24
mr

SUSPENSION

Front suspension	Tele	scopic fork
Front shock Re	bound/compression	adjustable
Front fork travel		120 mm

Rear suspension	Monocross/
Rear shock Rebound/compression	adjustable
Rear shock travel	65 mm
Front wheel travel	120 mm
Rear wheel travel	
Front tyre size	20/70 ZR17
Rear tyre size	80/55 ZR17

FRONT WHEEL

Rim size												MT3.50 x 17
Rim mate	ria	1								٠	•	. Aluminium

REAR WHEEL

Rim size			 					M15.50 x 1/
Rim materia	١.	 •						. Aluminium

BRAKES

Front brake type . . . Dual disc brakes (298 mm) Rear brake type . . . Single disc brake (245 mm)

Always wear a helmet, eye protection and protective clothing.

Yamaha encourage you to ride safely and respect fellow riders and the environment.

Specifications and appearance of Yamaha products shown here may vary according to requirements and conditions, and are subject to change without notice.

For further details, please consult your Yamaha dealer.

DEALER

Yamaha Motor (U.K.) Ltd.

Sopwith Drive The Brooklands Industrial Park Brooklands, Weybridge, Surrey KT13 OUZ



